



Gulf Coolant 40

Ready to use Coolant (Premixed with Water)

Product Description

Gulf Coolant 40 is "**British Standard coolant**" based on Mono Ethylene Glycol (MEG) and suitable corrosion inhibitors to provide protection against frost and corrosion. It is mixed with 60% of demineralized water for using as ready to use cooling and heat transfer fluid in internal combustion engines. It is free from potentially harmful additives such as nitrites, amines and phosphates and hence it contributes to a safer environment. It is neutral towards gaskets, hoses and provides good resistance against foam.

Features & Benefits

- It is formulated to provide effective corrosion protection to cooling system and engine parts made out of ferrous and non-ferrous metals.
- It provides round the year protection against frost and boiling
- It is compatible with seals.
- As it is free from nitrites, amines and phosphates, it contributes to safer environment.

Applications

- It is recommended for use in cooling systems of all types of liquid cooled automotive and industrial engines where such types of coolants are used. (Please refer OEM manual for recommended coolant)

Warning: Keep all antifreezes out of reach of children. Do not drink antifreeze. If swallowed, induce vomiting and immediately seek medical advice.

Specifications, Approvals & Typical Properties:

| Meets the following Specifications | | |
|--|-------------|----------------|
| BS 6580:1992, BS 6580:2010* | X | |
| Typical Properties | | |
| Test Parameters | ASTM Method | Typical Values |
| Density @ 20°C, Kg/L | D 4052 | 1.068 |
| Freezing point °C (40% antifreeze and 60% water) | D 1177 | -28 |
| Colour | Visual | Blue |
| pH @ 20°C (40% in water) | D 1287 | 8.2 |

*for product containing 25% or more MEG, BS 6580:2010 requires the addition of minimum 25 ppm of denatonium benzoate (bitterant), or the package has to be fitted with a childproof closure.

June 2016

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com