



Vecton Fuel Saver 5W-30 E6/E9

Helps Maximise Performance

Description

New Castrol Vecton Fuel Saver 5W-30 E6/E9 is a full synthetic Low SAPS engine oil formulated with unique System 5 Technology™ delivering up to 40% better performance¹ in the latest European diesel engines including Euro 6 and engines fitted with DPF. It also gave up to 1% fuel saving² in a Euro 5 engine using the European Transient Cycle test when compared to a modern top tier 15W-40 engine oil.

Application

Castrol Vecton Fuel Saver 5W-30 E6/E9 is designed for better fuel economy in the latest Euro 6 diesel engines. It is also suitable for extended service intervals as recommended by many European engine manufacturers, including Mercedes-Benz and Volvo, and is approved for use in MAN Euro 6 engines. It can be used in low emission Euro 4 & Euro 5 European trucks and buses, especially those requiring a low SAPS lubricant and in older on-road and off-road vehicles and equipment that require this performance level.

Advantages

Castrol Vecton Fuel Saver 5W-30 E6/E9 with unique System 5 Technology™ adapts to changing engine conditions and fights to help maximise performance in five key areas: fuel consumption, oil consumption, oil drain interval, component life and power. It also:

- Delivers real world fuel savings without compromising engine protection.
- Fights wear to critical engine components even at low viscosity.
- Fights piston deposits helping to reduce oil consumption.
- Fights harmful acids which form during engine operation.
- Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation.

1. In independent laboratory tests, Castrol Vecton Fuel Saver 5W-30 E6/E9 performed up to 40% better than API and ACEA industry standard limits across oil thickening, piston deposits, soot handling and wear and corrosion. See www.castrolvecton.com

2 Castrol Vecton Fuel Saver 5W-30 E6/E9 also gave up to 0.72% fuel saving when compared to a 10W-40 in the same test. Actual fuel economy depends on the type of vehicle, the driving style and the driving conditions. Results may vary. See www.castrolvecton.com

Typical Characteristics

Name	Method	Units	Vecton Fuel Saver 5W-30 E6/E9
Density @ 15C	ASTM D4052	g/ml	0.854
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.8
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6070
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	69.5
Viscosity Index	ASTM D2270	None	166
Ash, Sulphated	ASTM D874	% wt	1.0
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.5
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	228

Product Performance Claims

ACEA E6, E7, E9
API CJ-4
JASO DH-2
CAT ECF-3
Cummins CES 20081
Deutz DQC IV-10LA
Mack EO-M Plus, EO-N Premium Plus, EO-O Premium Plus
MAN M 3271-1 M 3477 M 3677
MB-Approval 228.31/ 228.51
MTU Oil Category 3.1
RVI RLD-3
Volvo CNG VDS 4
Scania LDF-4
Meets Ford WSS-M2C213-A1
For Iveco trucks requiring ACEA E6, E7, E9
Meets DAF PX Euro VI requirements

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Vecton Fuel Saver 5W-30 E6/E9

12 Jan 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk