

Q8 Dynobear 150

Excellent multi-purpose circulating oil

Description

Q8 Dynobear 150 is an excellent multi-purpose circulating lubricant developed for machine tools and general equipment. It has a certain additive that reduces friction and eliminates stick-slip and judder that might occur in mechanical and hydraulic machines. Q8 Dynobear 150 has outstanding rust- and corrosion protection, excellent anti-wear characteristics and high chemical and thermal stability.

Applications

Q8 Dynobear 150 is used as vacuum pump oil and in medium duty gear boxes. Q8 Dynobear range is highly recommended for machine tools and general equipment lubrication. It is suited for headstocks, carriage ways, cross feeds saddles and automatic pressures fed slideway lubricators.

Benefits

Decreased downtime thanks to increased maintenance efficiency

Limited products needed thanks to versatile applications of lubricants

Features

Excellent decrease of friction

Prevents sticking

Extremely fit for different operations

Specifications & Approvals

DIN	51517-2 CL	ISO	6743-2 F
DIN	51524-1 HL		

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	150
Density, 15 °C	D 4052	g/ml	0,886
Kinematic Viscosity, 40 °C	D 445	mm ² /s	150
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.6
Viscosity Index	D 2270	-	96
Flash Point, COC	D 92	°C	276
Colour	D 1500	-	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.