

# Q8 T 65 75W-90

Synthetic API GL-5 axle fluid

## Description

Q8 T 65 75W-90 is a superior synthetic axle lubricant. The product provides extreme protection due to its low operating temperature capability and oxidation resistance and facilitates easy gear shifting. The lubricant is formulated for heavy duty equipment such as rear-axes, final drives and selected manual transmissions, requiring special low temperature fluidity.

## Applications

Q8 T 65 75W-90 is designed for heavy duty equipment such as rear-axes, final drives and selected manual transmissions, requiring special low temperature fluidity. It meets the requirements of the API GL-5 specification.

## Benefits

- Full synthetic formulation to provide an extreme thermal stability.
- Superb fuel economy benefits, especially when used in axles.
- Reduces drive-line operating temperatures.
- Outstanding internal friction reduction.
- Outstanding protection against rust and corrosion.

## Specifications, recommendations and approvals

<b>API</b>	GL-5	<b>MB</b>	235.0
<b>Clark</b>	ALC-1 5M 7-80 KE	<b>Rockwell International</b>	O-76-E
<b>Clark</b>	TLC-25 3M 8-83	<b>Tatra</b>	<b>TDS 100/40</b>
<b>Eaton/Fuller</b>	Bulletin 2052	<b>Volvo</b>	97312 (<2013)
<b>Eaton/Fuller</b>	Bulletin 2053	<b>ZF</b>	TE-ML 05A
<b>Eaton/Fuller</b>	Form 121	<b>ZF</b>	TE-ML 07A
<b>Ford</b>	M2C 175-A	<b>ZF</b>	TE-ML 12A
<b>GM</b>	1940759 (90188629)	<b>ZF</b>	TE-ML 17B

Color code blue = officially approved

## Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Viscosity Grade	-	-	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	92,8
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14,07
Viscosity Index	D 2270	-	156
Brookfield Viscosity, -40 °C	D 2983	Pa.s	98
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	162

The figures above are not a specification. They are typical figures obtained within production tolerances.